



# SolarEdge Three Phase Inverters for Residential Installations for Australia

SE5K - SE8K

INVERTERS



## Specifically designed to work with power optimisers

- Noise level suitable for residential environment – No external fan
- Superior efficiency (98%)
- Small, lightest in its class, and easy to install
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless (Wi-Fi, ZigBee Gateway, Cellular)
- IP65 – Outdoor and indoor installation
- Fixed voltage inverter for longer strings
- Smart Energy Management control
- Integrated DC Safety Unit - Eliminates the need for external DC isolators



# SolarEdge Three Phase Inverters for Residential Installations for Australia

## SE5K-SE8K<sup>(1)</sup>

	SE5K	SE7K	SE8K	
<b>OUTPUT</b>				
Rated AC Power Output	5000	7000	8000	VA
Maximum AC Power Output	5000	7000	8000	VA
AC Output Voltage - Line to Line / Line to Neutral (Nominal)	400 / 230			Vac
AC Output Voltage - Line to Neutral Range	184 - 264.5			Vac
AC Frequency	50/60 ± 5			Hz
Maximum Continuous Output Current (per Phase)	8	11.5	13	A
Grids Supported - Three Phase	3 / N / PE (WYE with Neutral)			V
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes			
<b>INPUT</b>				
Maximum DC Power (Module STC)	6750	9450	10800	W
Transformer-less, Ungrounded	Yes			
Maximum Input Voltage per Array	600			Vdc
Nominal DC Input Voltage per Array	400			Vdc
Maximum Input Current	8.5	12	13.5	Adc
Reverse-Polarity Protection	Yes			
Ground-Fault Isolation Detection	700kΩ Sensitivity			
Maximum Inverter Efficiency	98			%
European Weighted Efficiency	97.3	97.4	97.6	%
Nighttime Power Consumption	< 2.5			W
<b>ADDITIONAL FEATURES</b>				
Supported Communication Interfaces <sup>(2)</sup>	RS485, Ethernet, ZigBee (optional), Wi-Fi (optional), Cellular (optional)			
Smart Energy Management	Export Limitation, Home Energy Management			
<b>STANDARD COMPLIANCE</b>				
Safety	IEC62109, AS/NZS3100			
Grid Connection Standards	AS/NZS4777:2015			
Emissions	IEC61000-6-2, IEC61000-6-3 , IEC61000-3-11, IEC61000-3-12, FCC part15 class B			
RoHS	Yes			
<b>INSTALLATION SPECIFICATIONS</b>				
AC output conduit size / Wire cross section	20mm minimum / 3-13mm <sup>2</sup>			
DC input conduit size / Wire cross section	20mm minimum / 3-13mm <sup>2</sup>			
DC Input	Terminal blocks for 2 arrays enclosed through 2 separate conduits <sup>(3)</sup>			
Dimensions with Safety Switch (H x W x D)	775 x 315 x 191			mm
Weight	24.7			kg
Operating Temperature Range	-20 - +60 <sup>(4)</sup>			°C
Cooling	Internal fan			
Noise	< 40			dBA
Protection Rating	IP65 - Outdoor and Indoor			
Bracket Mounted (Bracket Provided)				

<sup>(1)</sup> These specifications apply to inverters with part number SEK-AU00Exxxx

<sup>(2)</sup> Refer to Datasheets -> Communications category in Downloads page for specifications of optional communication options: <http://www.solaredge.com/groups/support/downloads>

<sup>(3)</sup> Two arrays must be connected to the inverter; refer to image below.

For complete design guidelines refer to: [http://www.solaredge.com/sites/default/files/se\\_inverter\\_installation\\_guide\\_e\\_series\\_addendum\\_aus.pdf](http://www.solaredge.com/sites/default/files/se_inverter_installation_guide_e_series_addendum_aus.pdf)

<sup>(4)</sup> For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>

